


s)

" Ultra-low capacitance: C

 $C_j = 0.35\text{pF typ}$ " Ultra-low leakage current: $I_R < 1\text{nA typ}$ " Low clamping voltage: $V_{CL} = 14\text{V typ. @ } I_{PP} = 16\text{A}$
(TLP)

" Solid-state silicon technology


Mechanical Data

" Package : DFN0603-2L

" Terminals : Tin plated leads, solderable per
J-STD-002 and JESD22-B102

" Polarity: Cathode line denotes the cathode end

" Marking: U5

Definitions of Electrical Characteristics

ESDULC5V0LZB

Maximum Ratings

PARAMETER	SYMBOL	Rating	UNIT
-----------	--------	--------	------

Peak pulse power ($t_p = 8/20$)

vCharacteristics (Typical)


8/20 μ s waveform per IEC61000 4 5

ESDULC5V0LZB

ESD clamping
(+8kV contact discharge per IEC61000 # 2)

ESD clamping
(8kV contact discharge per IEC61000 # 2)

TLP Measurement



vOutline Dimensions



6 \ P E R O	P L Q	P P	0 D
\$			
%			
&			
&			
(			
)			
*			

P P

ESDULC5V0LZB

Recommend Land Pattern (Unit:mm)

Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.