



YJB240G10M

N-Channel Enhancement Mode Field Effect Transistor

Product Summary

V_{DS}	100V
I_D	240A
$R_{DS(ON)}$ (at $V_{GS}=10V$)	2.6m
$R_{DS(ON)}$ (at $V_{GS}=6V$)	3.1m
100% EAS Tested	
100% V_{DS} Tested	

General Description

Split Gate Trench MOSFET technology
Excellent package for heat dissipation
High density cell design for low $R_{DS(ON)}$
Moisture Sensitivity Level 1
Epoxy Meets UL 94 V-0 Flammability Rating
Halogen Free

Applications

Load switch
Battery management
Solar

Absolute Maximum Ratings ($T_A=25$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-source Voltage	V		



YJB240G10M

Electrical Characteristics ($T_J=25$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
-----------	--------	------------	-----	-----	-----	-------



YJB240G10M

Typical Electrical and Thermal Characteristics Diagrams





Figure 1. Output Characteris 38.0/2s 38ms

apuacianCh racteris 38.0/2s 38ms



YJB240G10M




Figure 7. RDS(on) VS Drain Current




Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation



YJB240G10M




Figure 13. Maximum Transient Thermal Impedance




Figure 14. Safe Operation Area

Test Circuits & Waveforms





Figure A. Unclamped Inductive Switching (UIS) Test Circuit & Waveform



YJB240G10M


TO-263-B Package information



NOTE:
 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
 2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
 3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

UNIT: mm

Marking Information



Note

1. All marking is at middle of the product body
2. All marking is in laser printing
3. YJB240G10M is part no., YYWW is date code, "YY" is year, "WW" is week
4. Body color: Black



YJB240G10M

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com> , or consult your nearest Yangjie's sales office for further assistance.