



SMB3Z6.8AQ THRU SMB3Z220AQ

Surface Mount Zener Diodes

Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Part no. with suffix "Q" means AEC-Q101 qualified

Mechanical Data

- **Package:** DO-214AA (SMB)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (T_a=25 °C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MAX
DC power dissipation at T _L = 75 °C	P _D	W	3.0
Maximum instantaneous forward voltage@ I _F =200mA	V _F	V	1.5
Maximum junction temperature	T _J		-55 to +150

Storage temperature range

T_{stg}

SMB3Z6.8AQ THRU SMB3Z220AQ

SMB3Z6.8AQ THRU SMB3Z220AQ

60% = \$4 7+58 60% = \$4

v2UGHULQJ ,QIRUPDWLRQ

35() (5(' 3 1	3\$&.,1* &2' (	81,7 : (,*+7 J	0,1,080 3\$&.\$*(SFV	287(5 &\$5721 48\$17,7< SFV	'(/,9(5< 02' (
60% = \$4 a60% =	\$4)				

v0DUNLQJ ,QIRUPDWLRQ

v2XWOLQH 'LPHQVLRQV

'2 \$\$ 60%		
	0 L Q	0 D
\$		

v 6XJJHVWHG SDG OD\RXW

