



Surface Mount Schottky Rectifier



Features

- ✕ Guardring for over voltage protection
- ✕ Low power losses
- ✕ Extremely fast switching
- ✕ High forward surge capability
- ✕ High frequency operation
- ✕ Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- ✕ Part no. with suffix 01 means AEC-Q101 u0002 and JESD22-B102
- ✕ Polarity: Color band denotes the cathode end



■Maximum Ratings (Ta = 25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	SS310Q
Device marking code			SS310
Repetitive peak reverse voltage	V_{RRM}	V	100
Maximum RMS voltage	V_{RMS}	V	70
Maximum DC blocking voltage	V_{DC}	V	100
Maximum average forward rectified current (Fig. 1)	I_O	A	3.0
Surge(non-repetitive)forward current @ 60Hz half-sine wave, 1 cycle	I_{FSM}	A	80
Voltage rate of change (rated)	dV/dt	V/μs	10000
Storage temperature	T_{stg}	°C	-55 ~ +175
Junction temperature and storage temperature	T_J	°C	-55 ~ +175

■Electrical Characteristics Ta = 25°C Unless otherwise specified

PARAMETER	SYMBOL	TEST CONDITIONS	TYP	MAX	UNIT
Instantaneous forward voltage	V_F	$I_F = 3A$	$T_J = 25^\circ C$	0.76	V
			$T_J = 125^\circ C$	0.63	
Reverse current	I_R	Rated V_R	$T_J = 25^\circ C$	-	μA
			$T_J = 125^\circ C$	30	
Typical junction capacitance	C_J	$V_R = 4V, f = 1MHz$	95	-	pF



Thermal Characteristics $T_a = 25^{\circ}\text{C}$



SS310Q

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, functionality or otherwise.

The product listed herein is designed to be used with automobiles, are not designed for use in medical, life sustaining, or military applications. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use of sale.

This publication supersedes and replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for assistance.