

## Typical Applications

For use in general purpose rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, and telecommunication.

## Mechanical Data

**Package:** DO-204AC(DO-15)

Molding compound meets UL 94 V-0 flammability rating,  
RoHS-compliant

**Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

**Polarity:** Color band denotes cathode end

## Maximum Ratings (Ta=25 Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	RL201G	RL202G	RL203G	RL204G	RL205G	RL206G	RL207G
Device marking code			RL201G	RL202G	RL203G	RL204G	RL205G	RL206G	RL207G
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	$V_{RMS}$	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	$V_{DC}$	V	50	100	200	400	600	800	1000
Average Forward Current @60Hz sine wave, Resistance load, Ta =60	$I_{F(AV)}$	A	2.0						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Tj=25	$I_{FSM}$	A	70						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25			120						
Current squared time @1ms t8.3 ms Tj=25 Rating of per diode	$I^2t$	A <sup>2</sup> s	20.335						
Typical junction capacitance @ Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	$C_j$	pF	13						
Storage Temperature	$T_{stg}$		-55 ~ +150						
Junction Temperature	$T_j$		-55 ~ +150						

## Electrical Characteristics Ta=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	RL201G	RL202G	RL203G	RL204G	RL205G	RL206G	RL207G
Maximum instantaneous forward voltage drop per diode	$V_F$	V	$I_{FM}=2.0A$	1.1						
Maximum DC reverse current at rated DC blocking voltage per diode	$I_R$	$\mu A$	$T_j=25$	2.5						
			$T_j=125$	50						

v7KHUPDO & KDUDÄFWHU&QVHLFVVRWKHUÅLVH VSHFLILHG


3\$5\$0(7(5

6<0%2/

81,7



Outline Dimensions



Dimensions in millimeters

DO-204AC(DO-15)		
Dim	Min	Max
A	5.80	7.60
B	2.60	3.60
C	25.4	/
D	0.70	0.90



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damage or injury caused by the use of the product.